

Ahlstrom-Munksjö

# FibRoc<sup>®</sup>

## Ceiling

## Solutions for Perforated Wood & Metal Ceilings

Ahlstrom-Munksjö is a leading, global manufacturer of high performance fiber-based solutions, supplying products to the ceiling industry for over 40 years.

Our unique wet-laid and proprietary foam forming manufacturing technologies, experienced personnel, plus our reliable and extensive product range guarantee production of high quality ceilings.

Ahlstrom-Munksjö's FibRoc<sup>®</sup> nonwovens range is used as backings to perforated wood & metal ceilings and deliver unbeatable performance in noise reduction and fire resistance.

Ahlstrom-Munksjö FibRoc<sup>®</sup> Ceiling nonwoven product range includes nonwovens made of cellulose/glass blends and 100% glass.

### Benefits

- ✔ **Noise reduction** – excellent level of noise reduction, delivering acoustic comfort within a room
- ✔ **Fire resistance** – ensuring compliance with all necessary safety standards
- ✔ **Controlled rigidity, permeability and thickness** – enabling optimized ceiling manufacturing
- ✔ **Exceptional dimensional stability and strength** – delivering stability and strength for final ceiling product
- ✔ **Highly flexible** – no issues for curved ceilings
- ✔ **Dust free** – prevents dust from the plenum falling onto the floor

## Ahlstrom-Munksjö cellulose/glass nonwoven product range

High efficiency Ahlstrom-Munksjö nonwovens contain cellulose and glass fiber blends and tailor-made binder formulations.

### Typical product references:

Grade	Description	Basis weight g/m <sup>2</sup>	Colour	Calorific Value, PCS rating (ISO 1716) MJ/kg	Air permeability l/m <sup>2</sup> s
<b>BR7164046</b>	Cellulose/glass nonwoven with chemical binder and fire-retardant additive	46	Black	12,2	1500

Available in basis weights from 30 to 150g/m<sup>2</sup>. Black, white colors available as standard. Other colors available on demand. Widths up to 2400mm, roll diameter up to 1150mm

## Ahlstrom-Munksjö glass nonwoven product range

High efficiency Ahlstrom-Munksjö glass nonwovens contain glass fibers and tailor-made binder formulations. Glass fibers in the nonwovens are available with various diameters (6-16 microns) and lengths (6-20mm).

### Typical product references:

Grade	Description	Basis weight g/m <sup>2</sup>	Colour	Air permeability l/m <sup>2</sup> s
<b>GFT-93G10A-60</b>	Glass nonwoven	60	White	4300
<b>BWG-93G10A-60</b>	Glass nonwoven	60	Black	4300

G = 10 micron fiber. Available in basis weights from 15 to 130g/m<sup>2</sup>. Widths up to 4200mm. Standard core inner diameter: 152mm. Standard roll outer diameter: 1200mm

### Ahlstrom-Munksjö manufacturing platforms:

**Karhula, Finland | Tver, Russia | Brignoud, France**

Our manufacturing units are certified by SGS having ISO9001, ISO14001, ISO18001.

**Contact Ahlstrom-Munksjö Sales:** ✉ fibroc@ahlstrom-munksjo.com

**[www.ahlstrom-munksjo.com](http://www.ahlstrom-munksjo.com)**



Disclaimer: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed, including without limitation any warranty of merchantability or fitness for use. All users of the material are responsible for ensuring that it is suitable for their needs, environment and end use. All data is subject to change as Ahlstrom-Munksjö deems appropriate.