

Ahlstrom

FibRoc[®] Flooring

Solutions for Heavy Duty Floorings

Ahlstrom is a leading, global manufacturer of high performance fiber-based solutions, supplying products to the flooring industry for over 40 years.

Heavy duty floorings need to be robust and highly durable for extreme use, as well as having style and comfort for e.g. offices, hospitals, hotels, sport, safety and buses.

Our unique wet-laid and proprietary foam forming manufacturing technologies, experienced personnel, plus our reliable and extensive product range guarantee production of high quality floorings.

Ahlstrom FibRoc[®] nonwoven product range for heavy duty floorings is the widest in the market with a large combination of fibers: 100% glass, glass/cellulose providing good smoothness and low permeability, glass/polyester enabling flexible and resilient floorings and polyester/cellulose.

Our polyester/cellulose nonwovens can also be used in combination with scrim reinforcement delivering strong internal cohesion to the final flooring product.

Benefits

- ✔ **Exceptional dimensional stability and strength** – delivering stability and strength for final flooring product
- ✔ **Controlled rigidity, permeability and thickness** – enabling optimized flooring manufacture
- ✔ **Excellent compatibility with plastisol** – delivering smooth surface for enhanced gravure printability
- ✔ **Extensive and sustainable product range** – offering formaldehyde free and biodegradable binder solutions
- ✔ **Versatile manufacturing technology** – enabling flexible development and customized solutions for customers
- ✔ **Security of supply** – several qualified manufacturing platforms

Ahlstrom glass nonwoven product range for flooring manufacturers

Ahlstrom glass nonwovens contain glass fibers and tailor-made binder formulations. Glass fibers in the nonwovens are of various diameters (6-16 microns) and lengths (6-20mm). Available in basis weights from 15 to 130g/m².

Typical product references:

Grade	Description	Basis weight g/m ²	Thickness mm	Air permeability l/m ² s
AW-933G033-35	Glass nonwoven with surface binder G = 10 micron glass fiber	35	0.30	5600
GFT-93G10-60	Glass nonwoven G = 10 micron glass fiber	60	0.47	4100
GFT-93GD10-75	Glass nonwoven GD = 6 and 10 micron glass fiber blend	75	0.56	3000

Widths up to 4200mm, Standard core inner diameter: 152mm, Standard roll outer diameter: 1200mm

Ahlstrom glass/cellulose nonwoven product range for flooring manufacturers

Ahlstrom nonwovens contain glass and cellulose fibers and tailor-made binder formulations. **Our unique glass/cellulose nonwovens provide good smoothness and low permeability.** This product range is also an excellent solution to replace mineral felt in flooring applications. Available in basis weights from 30 to 130g/m².

Typical product references:

Grade	Description	Basis weight g/m ²	Thickness mm	Air permeability l/m ² s
GPFT-77G10C80-40	Glass/cellulose nonwoven G = 10 micron glass fiber	40	0.34	3450
AWP-93G043C7-60	Glass/cellulose nonwoven with surface binder G = 10 micron glass fiber	60	0.45	1750
NGP-93G2P15C7-60	Glass/cellulose nonwoven with pigment coating G = 10 micron glass fiber	60	0.43	2100

Widths up to 4200mm, Standard core inner diameter: 152mm, Standard roll outer diameter: 1200mm

Ahlstrom glass/polyester nonwoven product range for flooring manufacturers

Ahlstrom nonwovens contain glass and polyester fibers and tailor-made binder formulations. **This solution enables flexible and resilient floorings.** Available in basis weights from 30 to 120g/m².

Typical product references:

Grade	Description	Basis weight g/m ²	Thickness mm	Air permeability l/m ² s
GEFT-933G10A-35	Glass/polyester nonwoven G = 10 micron glass fiber	35	0.32	5500
AWE-933G032-50	Glass/polyester nonwoven with surface binder G = 10 micron glass fiber	50	0.42	4600

Widths up to 4200mm, Standard core inner diameter: 152mm, Standard roll outer diameter: 1200mm

Ahlstrom wetlaid nonwoven product range for scrim reinforcement manufacturers

For floorings requesting higher performances (safety, sports), Ahlstrom has developed a cellulose/polyester nonwoven with a highly controlled and stable porosity leading to higher productivity at scrim producers and less cleaning.

Our nonwoven also ensures strong internal cohesion to avoid delamination between the different layers in the final flooring product.

Typical product references:

Grade	Description	Basis weight g/m ²	Thickness mm	Air permeability l/m ² s
BR6818025	Polyester/cellulose nonwoven with a soft binder	25	0.093	1800
BR6832020	Polyester/cellulose nonwoven with a stiff binder	20	0.096	2050
BR6834030	Polyester/cellulose nonwoven with a stiff binder	30	0.122	1200

Widths up to 2400mm, roll diameter up to 1150mm

Ahlstrom manufacturing platforms:

Karhula, Finland | Brignoud, France

Our manufacturing units are certified by SGS having ISO9001, ISO14001, ISO18001.

Contact Ahlstrom Sales: ✉ fibroc@ahlstrom.com

www.ahlstrom.com



Disclaimer: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed, including without limitation any warranty of merchantability of fitness for use. All users of the material are responsible for ensuring that it is suitable for their needs, environment and end use. All data is subject to change as Ahlstrom deems appropriate.