



## Oil Filter Media

**As a leader in automotive and heavy duty filtration applications, Ahlstrom-Munksjö has always been at the forefront of high performance filter media.**

Our complete portfolio provides a full range of products to the filter manufacturers. Products range from cellulose to high synthetic and full synthetic solutions. They offer improved performance in hot oil and are suitable for next generation applications.

Ahlstrom-Munksjö has the filter media you need for your engine oil applications.

- Full portfolio of oil media for any application
- High hot oil performance to meet the most demanding specifications
- New innovative self-support synthetic media available
- Highest levels in filtration performance with 300 and 400 series

Our high efficiency oil media and new self-support products bring unique answers to the oil filtration market. Ahlstrom-Munksjö Duralube™ 3S is designed to work under the most challenging conditions. It offers significant cost savings in terms of materials used and in the processing time

## Features and Benefits

- ✔ High hot oil life performance
- ✔ Longer service intervals to reduce maintenance costs
- ✔ Best in class efficiency and dirt holding capacity
- ✔ Self-supporting to reduce manufacturing costs and improve flexibility of filter design
- ✔ Range of curing levels appropriate to many applications
- ✔ Global supply platform

## End use applications

- ✔ Heavy duty oil
- ✔ Automotive oil

Products	Media Technology	Chemistry	Features and Benefits
<b>100 Standard</b>	Wet laid 100% cellulose and cellulose + glass	No cure/Advance cure Phenolic cured Fast Cure	<ul style="list-style-type: none"> <li>• Standard oil media</li> <li>• Good hot oil burst</li> <li>• Good DHC and efficiency</li> </ul>
<b>200 High Hot Oil Resistance</b>	Wet laid 100% cellulose and cellulose + glass with PET	No cure/Advance cure Phenolic cured Fast Cure	<ul style="list-style-type: none"> <li>• Long life oil media</li> <li>• Improved hot oil burst</li> <li>• Improved DHC and efficiency</li> </ul>
<b>300 100% Synthetic</b>	Wet laid 100% PET Trinitex 100% glass	No cure/Advance cure Phenolic cured Fast Cure	<ul style="list-style-type: none"> <li>• Premium oil media</li> <li>• Highest performance hot oil burst</li> <li>• High levels filtration performance</li> <li>• High pleat stability and self supporting</li> </ul>
<b>400 Self Support 100% Synthetic</b>	Ahlstrom-Munksjö Duralube™ 3S	No cure/Advance cure Phenolic cured Fast Cure	<ul style="list-style-type: none"> <li>• Synthetic self-supporting media</li> <li>• Highest levels filtration performance</li> <li>• High pleat stability and self supporting</li> </ul>

Contact Ahlstrom-Munksjö Sales: ✉ [filtration@ahlstrom-munksjo.com](mailto:filtration@ahlstrom-munksjo.com)

[www.ahlstrom-munksjo.com](http://www.ahlstrom-munksjo.com)



Disclaimer: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed, including without limitation any warranty of merchantability of fitness for use. All users of the material are responsible for ensuring that it is suitable for their needs, environment and end use. All data is subject to change as Ahlstrom-Munksjö deems appropriate.